


TECHNICAL SPECIFICATIONS

Ex FLOODLIGHT IIC



TYPE OF PROTECTION

Ex db

Ex tb

Ex op is

LED



ZONE | LEVEL
1 | Gb

ZONE | LEVEL
21 | Db



2 | Gb

22 | Db



Gas Group

IIA
IIB
IIC

Dust Group

IIIA
IIIB
IIIC

Ex FLOODLIGHT
IIC

ExFL-IIC 60W
110-230VAC

ExFL-IIC 80W
110-230VAC

ExFL-IIC 100W
110-230VAC

ExFL-IIC 120W
110-230VAC

ExFL-IIC 140W
110-230VAC

ExFL-IIC 60W
24VAC

ExFL-IIC
100W 42VAC

Electrical Characteristics

Nominal Voltage	110 - 230 VAC					24 VAC	42 VAC
Operating Voltage	110 - 230 VAC					20 - 28 VAC	36 - 48 VAC
Total Power	60W	80W	100W	120W	140W	60 W	100 W
Power Factor	>0,87	>0,92	>0,92	>0,95	>0,96	>0,95	>0,95
Ambient Temperature	T6, T80°C Ta:-20°C to +50°C			T5, T85°C Ta:-20°C to +40°C T6, T80°C Ta:-20°C to +50°C		T6, T80°C Ta:-20°C to +50°C	

Light Technology Characteristics

Light distribution	60°, 90°, 120°, T2M, T3M		60°, 90°, 120°			60°, 90°, 120°, T2M, T3M	60°, 90°, 120°
Initial Total Lumens	~ 8600 lm	~ 11500 lm	~ 14300 lm	~17300 lm	~ 20100 lm	~ 7500 lm	~ 13500 lm
Luminary Efficacy	~ 143 lm/W at 5000 K					~ 125 lm/W at 5000 K	~ 135 lm/W at 5000 K
CCT	~5000 K (other light colors are optional)						
CRI	>80						

Protection & Construction

IP and IK Rating	IP66, IK08		
Protections	OVP, OTP, OCP		
Housing	Die-cast aluminium, powder coated, tempered glass 10mm		
Gasket	Silicone gasket		
Conecting Terminal	L, N, PE max 3x2.5mm², external PE terminal M5/4mm²		
Weight	10,20kg (without bracket)		
Bracket weight	0,90kg		
Cable entry M20x1.5	2x Ex glands or Ex gland and Ex plug		
Ex marking	II 2G Ex db op is IIC T6 Gb; II 2D Ex op is tb IIIC T80°C Db	II 2G Ex db op is IIC T5...T6 Gb II 2D Ex op is tb IIIC T85°C...T80°C Db	II 2G Ex db op is IIC T6 Gb; II 2D Ex op is tb IIIC T80°C Db
Dimensions	380x300x100mm		

▪ High color rendering index >80

▪ Beam angles of 60°, 90°, 120°, T2M, T3M

▪ Replaceable antistatic protective Peel off Foil

▪ Excellent thermal management

▪ Mounted on a cart, scaffold or wall


▪ Individual or daisy chain connection

datal.com




POLAR CURVE


Ex FLOODLIGHT 60°




Ex FLOODLIGHT 90°




Ex FLOODLIGHT 120°








Ex FLOODLIGHT T2M




Ex FLOODLIGHT T3M




DIMENSIONS, CONNECTION



ACCESSORIES



Ex Gland M20
ø6,5-11,9 mm or
ø10,0-14,3 mm



Antistatic
Protective peel off
Foil



Ex Stopping
Plug M20

DATA LINK d.o.o., Bjelovar
Blajburških žrtava 16, 43000 Bjelovar - Croatia
Phone: +385 (0)43 211 111
E-mail: info@datal.com

The content of the broadcast material are the sole responsibility of company DATA LINK.

The project is co-financed by the European Union from the European Regional Development Fund.

Together to EU funds



European Union



www.strukturnifondovi.hr

