



LED



GalaLED	BA02	LT01	LT03	LT23
Order No.	1001729	1002104	1002178	Available soon

Electrical Characteristics

Nominal Voltage	24-42VAC	24-42VAC	230VAC	230VAC
Operating Voltage	20 - 48VAC 20 - 60VDC	80 - 120VAC 90 - 130VDC	200 - 250VAC	200 - 250VAC
Total Power	~12W	~12W	~12W	~12W
Power Factor	>0,99 at 24VAC	>0,99 at 24VAC	~0,7 at 230VAC	~0,7 at 230VAC
Operating Temperature	-40°C to +50°C			

Light Technology Characteristics

Initial Total Lumens	~1300lm	~1300lm	~1300lm	~1300lm
Luminary Efficacy	~110lm/W	~110lm/W	~110lm/W	~110lm/W
CCT	~5000K			
CRI	80 - 85			

Protection & Construction

IP and IK Protection	IP66, IP67, IK10			
Protections	OVP, OTP			
Luminary Inner Protective Cover	PMMA 2.5mm			
Removable Protective Cover	Polycarbonate 2.5 - 3mm			
Housing	PMMA, PA6, PC, ABS			
Gasket	Silicone gasket			
Conecting Terminal	Piercing connector for flat cable			
Connection cable	H05RNH2-F 2x1.5mm ² or 2x2.5mm ²			
Fixture Weight	0,53kg	0,50kg	0,50kg	0,50kg
Lifespan(on 25°C)	50 000 hours			

▪ Mechanical protection grade IP66, IP67, IK10

▪ Voltages 24VAC, 48VAC, 230VAC

▪ High color rendering index 80-85

▪ Quick setup and removal

▪ Innovative pierce through mounting

▪ Individual or daisy chain connection

▪ Maintenance free

▪ High lumen output- 1300lm

▪ No glare effect

